



Lat Pull Down Machine

*The machine structure and accessories made of 50 mm x 50 mm, 60 mm x 40 mm or 100 mm x 50 mm ere tubes in 14 gauge for, rectangle & 10 gauge for bending frame.

* The machine structure and accessories will be powder C08,ted I painted.

*All pulleys will be of m.s. material with double ball bearing & chrome plated for smooth movement of the machine.

* Bearing used, are high graded lubricated z z steel bearings.

*All runner bars, handles will be of 25 mm & curling bars will be of 25 mm /28 mm, m. s. Hard chrome plated,

* PVC Coated 6 mm, high tension, high resistance wire rope will be used, for durability and safety.

* Machine weight plates are of m. s. hard chrome plated I m. s. nickel chrome plated I

m. s. powder coated I cast iron painted Of powder coated fitted with long lasting durable nylon 6 bushings.

*18 mm plywood will be used for seats & pads.

* Cushioning of high density foam for maximum comfort & safety, best quality refine will be provided in wide range of colors.

* High tensile strength stainless steel pins provided for weight stack.

* All handles will be covered with free revolving and excelled quality grips.

* All other plated parts will be provided with white nickel chrome plating of 0 microns.

* All powder coated parts will be provided with 60 microns coat and in wide range of colors.

